

WELCOME TO THE NEWHAVEN DESIGN ESSENTIALS

The Design Essentials form part of your Contract of Sale and should be referred to when designing your new home. They are intended to create an attractive streetscape that results in a cohesive, quality urban form, while not precluding individual design solutions.

Stockland encourages a variety of architectural styles and materials in the design of your home. Stockland reserves the right to vary the requirements of the Design Essentials at its discretion and approve works which do not comply with the Design Essentials where considered to be of merit.

The Design Essentials apply in addition to, and not in lieu of other statutory requirements. Approval from your Local Government Authority will still be required in addition to any approval issued by Stockland. Any Detailed Area Plans take precedent over these guidelines.

Several additional requirements apply to lots less than 13 metres in width.

Explanatory notes are included in the pack to provide clarification on elements of the Design Essentials.

THE DESIGN ESSENTIALS

1.	Primary Street Elevation	1.1	Homes shall have articulated façades by including at least 1 indentation or projection in the floor plan excluding the garage.		
		1.2	street elevation (minimum 20% of primary street elevation, excludes windows and doors). Bright or primary colours may not be used as the dominant colour.		
		1.3			
		1.4			
		1.5	For Lots less than 13m wide the following will apply:		
			1.5.1 At least one window of a habitable room overlooking the street or public reserve shall be incorporated in the primary façade.		
			1.5.2 An entry feature or room must be located forward of the garage where a double garage is proposed (excludes laneway access homes).		
			1.5.3 Where more than two adjacent dwellings are being constructed by the same owner, create identifiable differences in facades, however use of complementary materials and colour palette over the development is permitted.		
2.	Orientation	2.1	Unless varied by a Detailed Area Plan, dwellings must address nominated street/s and/or public reserve in terms of main entry, major openings, articulation, materials and architectural features. Homes directly abutting public reserve shall orientate as follows:		
			2.1.1 If vehicle access is via a laneway - the public reserve is considered as the primary façade.		
			2.1.2 If vehicle access is via a mews or street, this shall be considered the primary façade, however the secondary façade overlooking the public reserve must include the following:		
			 Articulation in the floor plan mirrored in the roof design. At least one architectural feature visible from the public reserve. 		
3.	Corner Lots	3.1	Homes located on corners shall address both streets through their design by extending the primary elevation features (colours/materials) onto the secondary street elevation where forward of a return fence.		
4.	Roofs	4.1	A minimum 24 degree pitch is required for hipped and gabled roofs.		
		4.2	A minimum of 8 degrees is required for skillion roofs (15 degree maximum).		
		4.3	Flat roofs are to be concealed from view on the primary/secondary elevation or from any public reserve by a parapet wall.		
		4.4	Eaves or window overhangs to a minimum dimension of 400mm are required to primary and secondary elevations (excluding secondary elevations facing south).		

5.	Carports/Garages	5.1	The roof and design features must be consistent with the form and materials of the home.
		5.1	Garages must not protrude more than 2m forward of the main building line (excludes laneways).
		5.2	Carports located forward of the main building line must have no more than one solid wall.
		5.3	Single garages/carports are permitted on lot widths less than 13m.
		5.4	Single, tandem garages are permitted on lot widths less than 13m.
6.	Driveways	6.1	All crossovers and driveways must be completed prior to occupation.
		6.2	Driveways must not be constructed from plain grey concrete.
7.	Fencing to Front & Secondary Streets	7.1	Front fencing as viewed from the street or a public space must not be higher than 1.8m and must be at least 50% visually permeable above 1.2m high. Materials and colours must be consistent or complementary to the primary street elevation's finishes.
		7.2	Fencing to a secondary street must be set back at least 4m from the corner truncation, constructed of Colorbond colour Teatree (unless otherwise approved by Stockland) and be a maximum of 1.8m high.
8.	Side & Rear	8.1	Is to be a maximum of 1.8m high.
	Fencing	8.2	Must be of Colorbond colour Teatree.
		8.3	Must return to the house a minimum of 1m behind the front façade.
9.	Retaining Walls	9.1	Where the developer has constructed a fence, entry statement or retaining wall, it must be maintained by the owner to the standard to which it was constructed and must not be modified without prior written consent of the developer.
10.	Developer Works	10.1	Where the developer has constructed a fence, entry statement or retaining wall, it must be maintained by the owner to the standard to which it was constructed.
11.	Outbuildings	11.1	All outbuildings and garden sheds must be constructed behind the front and/or secondary street building line unless it can be shown that they are not visible from the adjacent street or public area.
12.	Non-Ground Mounted Plant or Equipment	12.1	Roof mounted items visible from the street or public spaces must be minimal including but not limited to satellite dishes, TV aerials, external hot water services, water tanks, air conditioning units, heating units etc.
		12.2	Solar panels and collectors for hot water units are the exception to this standard when orientated to maximise their effectiveness.
13.	Ground Mounted Plant or Equipment	13.1	All ground mounted services are to be screened where visible from any street or public space including but not limited to heating and cooling units, rubbish disposal containers, swimming pool equipment, rain water tanks, clothes hoists and washing lines.
14.	Soakwells	14.1	Soakwells to be installed with sufficient capacity to store all captured rainwater for storms up to and including five (5) year events.

EXPLANATORY NOTES

Architectural Feature	Acceptable architectural features to comply with clause 2.1.2 may include a gambrel, gable-end, blade wall or any other feature visible from the public reserve.		
Articulated Façade	Variations to the elevation through projections and indentations in the floor plan resulting in the creation of shadows and depth to add visual interest.		
Carport	An open, self supporting structure or a structure under the main roof supported by posts, pillars or piers.		
Corner Lots	A corner lot is defined as being located at the junction of 2 streets, street and mews or at the junction of a street and public reserve.		
Entry Pergola	An entry feature with a separate permeable roof and supported by pillars or piers.		
Façade	A façade is the face of a building especially the primary or front elevation showing its most prominent architectural features.		
Habitable Room	Includes all living rooms, kitchens and bedrooms, but not bathrooms, WCs or circulation space.		
Laneway	Is a narrow local street type without a verge which is located along the rear and/or side property boundary. Vehicle access to garages should be from the laneway.		
Main Building Line	The main building line is measured from the front most habitable room on the primary street elevation not the projection of a feature.		
Mews	Is a narrow local street type without a verge which is located along the front of the property boundary.		
Primary Street	The front elevation of the home will be situated on the primary street which includes the main entry to the dwelling.		
Public Reserve	A public reserve is any parkland, bushland or wetland designated as public open space within the residential community.		
Return Fence	A return fence extends from the secondary street fencing to the side of the home.		
Secondary Street	The secondary street is the road which intersects or adjoins the primary street and does not include the main entry to the dwelling.		
Window Overhang	A window overhang is a structure built into the home that shades windows as a substitute to eaves.		

THE APPROVAL PROCESS

Step 1 - Stockland Design Essentials Approval

When designing your home, refer to the following documents:

- · Stockland Design Essentials.
- Contract of Sale, Individual Lot Plan and Detailed Area Plan (DAP), if applicable.
- Council and Other Government Codes or Regulations.

Upon completion, submit your finalised design via Stockland's online design assessment tool, i-Scope. Your application must include:

- Site Plan (min. scale 1:200) indicating North point, contour levels, finished floor levels and setbacks from all boundaries, total floor area and any proposed front fencing, earthworks or retaining walls where applicable.
- Floor Plans (min. scale 1:100) showing key dimensions and window positions.
- Elevations (min. scale 1:100) indicating building heights, roof pitches, eave depths, materials and all external plant and equipment (e.g. air conditioners.)

Stockland will issue a 'Full Design Approval' where the plans appropriately comply with the Design Essentials. Failure to comply with these Design Essentials will delay receival of your building license.

Where amendments are necessary, revised plans are to be re-submitted to Stockland for final approval before you can build.

Step 2 - Local Building Approval

Upon receipt of your approval from Stockland, an application can be made to the relevant authority to receive approval for building.

Additional Notes

- Applications will generally be assessed and responded to within 10 business days from day of receipt from Stockland. A written response will be sent to the builder notifying of the assessment outcome.
- Applications will not be assessed until all information as noted above has been supplied to Stockland.
- Builders are to submit plans for assessment via i-Scope only. Owner builders can submit plans to designapproval@stockland.com.au.

BUYER:	 BUYER:	
WITNESS:	 WITNESS:	
DATE:	 DATE:	
SELLER:	 	
WITNESS:	 	
DATE:		